

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP 45 AERO  
 Material number : 000000000000017400

**Manufacturer or supplier's details**

Company : Zep Inc.  
 Address : 350 Joe Frank Harris Parkway, SE  
 Emerson, GA 30137  
 Telephone : 404-352-1680

**Emergency telephone numbers**

**For SDS Information** : Compliance Services 1-877-428-9937  
**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded  
**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
 In the District of Columbia 202-483-7616

**Recommended use of the chemical and restrictions on use**

Recommended use : Lubricant

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	Aerosol containing a compressed gas
Colour	brown
Odour	characteristic

**GHS Classification**

Gases under pressure : Compressed gas  
 Skin irritation : Category 2  
 Eye irritation : Category 2A  
 Skin sensitisation : Category 1  
 Carcinogenicity : Category 1B  
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

**GHS label elements**

Hazard pictograms : 

Signal word : Danger

Hazard statements : H280 Contains gas under pressure; may explode if heated.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

H336 May cause drowsiness or dizziness.

H350 May cause cancer.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P403 Store in a well-ventilated place.

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

**Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Concentration [%]
trichloroethylene	79-01-6	>= 30 - < 50
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
Distillates (petroleum), straight-run middle	64741-44-2	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
carbon dioxide	124-38-9	>= 1 - < 5
pentyl acetate	628-63-7	>= 1 - < 5
2-methylbutyl acetate	624-41-9	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

---

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.  
In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do NOT induce vomiting.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.  
Chronic effects are delayed and symptoms may not be observed during an exposure.  
Causes skin irritation.  
Causes serious eye irritation.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.
- 

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
-

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

Hazardous combustion products	: Carbon dioxide (CO <sub>2</sub> ) Carbon monoxide Smoke Chlorine compounds
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling	: Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
-------------------------	--

## ZEP 45 AERO

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Keep in a cool, well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
trichloroethylene	79-01-6	TWA	10 ppm	ACGIH
		STEL	25 ppm	ACGIH
		TWA	100 ppm	OSHA Z-2
		CEIL	200 ppm	OSHA Z-2
		Peak	300 ppm	OSHA Z-2
		TWA	50 ppm 270 mg/m <sup>3</sup>	OSHA P0
		STEL	200 ppm 1,080 mg/m <sup>3</sup>	OSHA P0
		STEL	100 ppm 537 mg/m <sup>3</sup>	CAL PEL
		C	300 ppm	CAL PEL
		PEL	25 ppm 135 mg/m <sup>3</sup>	CAL PEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	10,000 ppm	OSHA P0

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

			18,000 mg/m3	
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
		PEL	5,000 ppm 9,000 mg/m3	CAL PEL
		STEL	30,000 ppm 54,000 mg/m3	CAL PEL
pentyl acetate	628-63-7	TWA	100 ppm 525 mg/m3	NIOSH REL
		TWA	100 ppm 525 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
2-methylbutyl acetate	624-41-9	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH

**Biological occupational exposure limits**

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
TRICHLOROETHENE	79-01-6	Trichloroacetic acid	Urine	End of shift at end of workweek	15 mg/l	ACGIH BEI
TRICHLOROETHENE		Trichloroethanol	In blood	End of shift at end of workweek	0.5 mg/l	ACGIH BEI
TRICHLOROETHENE		Trichloroethylene	In end-exhaled air	End of shift at end of workweek		ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a compressed gas

Colour : brown

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Boiling point : 87.22 °C

Flash point :  
Not applicable

Evaporation rate : < 1

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : Not applicable

Relative vapour density : No data available

Density : 1.137 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : Not applicable

Heat of combustion : 20.59 kJ/g

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Metals Oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Chlorine Phosgene Hydrogen chloride gas

---

**SECTION 11. TOXICOLOGICAL INFORMATION**
**Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Chronic effects are delayed and symptoms may not be observed during an exposure.

**Carcinogenicity:**

<b>IARC</b>	Group 1: Carcinogenic to humans	
	trichloroethylene	79-01-6
<b>ACGIH</b>	Suspected human carcinogen	
	trichloroethylene	79-01-6
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
<b>NTP</b>	Known to be human carcinogen	
	trichloroethylene	79-01-6

**Acute toxicity**
**Product:**

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
---------------------	---

**Components:**

<b>trichloroethylene:</b>	
Acute oral toxicity	: LD50 Oral Rat: 4,920 mg/kg



**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

- Acute inhalation toxicity : LC50 Mouse: 8450 ppm  
Exposure time: 4 h
- Acute dermal toxicity : LD50 Dermal Rabbit: > 20,000 mg/kg
- Distillates (petroleum), hydrotreated heavy naphthenic:**  
Acute oral toxicity : LD50 Rat: > 5,000 mg/kg
- Acute inhalation toxicity : LC50 Rat: > 5 mg/l  
Exposure time: 4 h
- Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: Irritating to skin.

**Serious eye damage/eye irritation****Product:**

Remarks: Severe eye irritation

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product:**

Remarks: No data available

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

**Components:****trichloroethylene :**

Partition coefficient: n-octanol/water : log Pow: 2.29

**2-(2-butoxyethoxy)ethanol :**

Partition coefficient: n-octanol/water : Pow: 1

**pentyl acetate :**

Partition coefficient: n-octanol/water : log Pow: 2.3

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

**SECTION 15. REGULATORY INFORMATION**

- TSCA list** : The following substance(s) is/are subject to a Significant New Use Rule:  
trichloroethylene 79-01-6
- The following substance(s) is/are subject to TSCA 12(b) export notification requirements:  
trichloroethylene 79-01-6

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
trichloroethylene	79-01-6	100	212

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Gases under pressure  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation  
 Respiratory or skin sensitisation  
 Carcinogenicity  
 Specific target organ toxicity (single or repeated exposure)

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

trichloroethylene	79-01-6	47 %
2-(2-butoxyethoxy)ethanol	112-34-5	4.3931 %
2-butoxyethanol	111-76-2	0.0669 %

**California Prop. 65**

WARNING: This product can expose you to chemicals including trichloroethylene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

**SECTION 16. OTHER INFORMATION**

**ZEP 45 AERO**


Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

**Further information**

**NFPA:**



**HMIS III:**

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>3</b>

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

**OSHA - GHS Label Information:**

Hazard pictograms :



Signal word :

**Danger:**

Hazard statements :

Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer.

Precautionary statements :

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.  
**Storage:** Store in a well-ventilated place. Protect from sunlight. Store in a well-ventilated place.  
**Disposal:** Disposal of contents/container in accordance with local regulation.

Version:	2.1
Revision Date:	02/09/2018
Print Date:	04/06/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

**ZEP 45 AERO**

Version 2.1

Revision Date 02/09/2018

Print Date 04/06/2018

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.