

SAFETY DATA SHEET

Issue Date 15-Oct-2005 Revision Date 28-Feb-2013 Version 1

1. IDENTIFICATION

Product Identifier

Product Name DLX Fuel Line De-Icer #90

Other Means of Identification

SDS # CALWIS-006

UN/ID No UN1219

Synonyms DLX Fuel Line De-Icer #90 DLX Fuel Line De-Icer #90-55

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Fuel additive.

Details of the Supplier of the Safety Data Sheet

Supplier Address Calwis Company 901 Hinkle Street Green Bay, WI 54303

Emergency Telephone Number

Company Phone Number 1-920-499-4990

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

| Serious eye damage/eye irritation | Category 2 |
|--|------------|
| Specific target organ toxicity (single exposure) | Category 3 |
| Flammable liquids | Category 2 |

Signal Word Danger

Hazard Statements

Causes severe eye irritation May cause respiratory irritation. May cause drowsiness or dizziness Highly flammable liquid and vapor





Appearance Transparent, colorless liquid

Physical State Liquid

Odor Characteristic alcohol odor

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed May be harmful if inhaled

Other Information

Not Applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms DLX Fuel Line De-Icer #90

DLX Fuel Line De-Icer #90-55.

| Chemical Name | CAS No | Weight-% |
|---------------------------|-------------|----------|
| Isopropyl alcohol | 67-63-0 | 99 |
| Non-hazardous Ingredients | Proprietary | 1 |

4. FIRST AID MEASURES

First Aid Measures

General advice If exposed or concerned: Get medical advice/attention.

Inhalation Remove to fresh air. Get medical attention if symptoms persist. Get medical attention if you

feel unwell.

Eye Contact Flush immediately eyes thoroughly with water for at least 15 minutes. If eye irritation

persists: Get medical advice/attention.

Induce vomiting if discovered within 2 hours. Call immediately a physician or your local

Poison Control Center.

Skin Contact Wash off immediately with soap and plenty of water. Get medical attention if necessary.

Remove contaminated clothing and shoes.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms May produce dermatitis and scaling on chronic skin contact.

Irritation of eyes and mucuous members.

Headache.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray (fog). Carbon dioxide (CO2). Dry chemical. Alcohol resistant foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Vapors are heavier than air and may travel along groung to ignition sources and flash back. Use water to keep fire-exposed structures and container cool.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO2).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Use personal protection recommended in Section 8.

Environmental Precautions See Section 12 for additional ecological information.

Methods and Material for Containment and Cleaning Up

Methods for Containment Eliminate all ignition sources. Contain spills in diking materials such as sandbags.

Methods for Cleaning Up For waste disposal, see section 13 of the SDS. Clean up in accordance with all applicable

regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. All equipment used when handling the product must be grounded. Use with adequate ventilation. Empty containers may contain flammable residual vapors. Wash face, hands, and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use spark-proof tools and explosion-proof equipment. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use personal protective equipment as required. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions Store in a well-ventilated place. Do not handle or store near any sources of ignition or

strong oxidants. Keep container tightly closed. Store locked up.

Incompatible Materials Oxidizing materials. Organic acids. Inorganic acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-------------------|---------------|--|------------------------------|
| Isopropyl alcohol | STEL: 400 ppm | TWA: 400 ppm | IDLH: 2000 ppm |
| 67-63-0 | TWA: 200 ppm | TWA: 980 mg/m ³ | TWA: 400 ppm |
| | | (vacated) TWA: 400 ppm | TWA: 980 mg/m ³ |
| | | (vacated) TWA: 980 mg/m ³ | STEL: 500 ppm |
| | | (vacated) STEL: 500 ppm | STEL: 1225 mg/m ³ |
| | | (vacated) STEL: 1225 mg/m ³ | |

Appropriate Engineering Controls

Engineering Controls Good general ventilation should be used. Apply technical measures to comply with the

occupational exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection Use chemical safety goggles if contact is likely.

Skin and Body Protection Wear suitable protective clothing.

Respiratory Protection No protective equipment is needed under normal use conditions.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or

smoke when using this product. Take off all contaminated clothing and wash it before reuse. Avoid contact with skin, eyes or clothing. Wash hands thoroughly after handling.

Avoid breathing (dust, vapor, mist, gas).

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Liquid

Appearance Transparent, colorless liquid Odor Characteristic alcohol

odor

ColorColorlessOdor thresholdNot determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH Not determined

Melting point/freezing point -89 °C / -127 °F

Boiling point/boiling range 82 °C / 180 °F

Flash point 11.7 °C / 53 °F CC (closed cup)
Evaporation rate 1.7 (butyl alcohol = 1)

Flammability (solid, gas) N/A- Liquid

Flammability limits in air

Upper flammability limits 12.7%

Lower flammability limit 2.5%

 Vapor pressure
 40 mmHg
 @ 24 ° C

 Vapor density
 2.1
 (Air=1)

 Specific gravity
 0.785
 (1=Water)

Water solubility Soluble in water Solubility in other solvents Not determined **Partition coefficient** Not determined **Autoignition temperature** 432.2 °C / 810 °F **Decomposition temperature** Not determined Kinematic viscosity Not determined Dynamic viscosity Not determined **Explosive properties** Not determined **Oxidizing Properties** Not determined

Other Information

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Oxidizing materials. Organic acids. Inorganic acids.

Hazardous Decomposition Products

Carbon oxides. Carbon monoxide. Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Inhalation May be harmful if inhaled.

Eye Contact Causes severe eye irritation.

Skin Contact Avoid contact with skin.

Ingestion May be harmful if swallowed.

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|-------------------|--------------------|-----------------------------|-----------------------|
| Isopropyl alcohol | = 4396 mg/kg (Rat) | = 12800 mg/kg (Rat) = 12870 | = 72.6 mg/L (Rat) 4 h |
| 67-63-0 | | mg/kg (Rabbit) | |

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Serious eye damage/eye irritation Causes severe eye irritation.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|-------------------|-------|---------|-----|------|
| Isopropyl alcohol | | Group 1 | | X |
| 67-63-0 | | Group 3 | | |

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

Numerical Measures of Toxicity- Product

Not determined

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4440 mg/kg
ATEmix (inhalation-gas) 25253 mg/l
ATEmix (inhalation-dust/mist) 73.3 mg/l
ATEmix (inhalation-vapor) 73.3 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal

| Chemical Name | Algae/aquatic plants | Fish | Toxicity to | Crustacea |
|-------------------|------------------------|---------------------------|----------------|---------------------------|
| | | | microorganisms | |
| Isopropyl alcohol | 1000: 96 h Desmodesmus | 9640: 96 h Pimephales | | 13299: 48 h Daphnia magna |
| 67-63-0 | subspicatus mg/L EC50 | promelas mg/L LC50 | | mg/L EC50 |
| | 1000: 72 h Desmodesmus | flow-through 11130: 96 h | | _ |
| | subspicatus mg/L EC50 | Pimephales promelas mg/L | | |
| | | LC50 static 1400000: 96 h | | |
| | | Lepomis macrochirus µg/L | | |
| | | LC50 | | |

Persistence and Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Not determined.

| Chemical Name | Partition coefficient |
|-------------------|-----------------------|
| Isopropyl alcohol | 0.05 |
| 67-63-0 | |

Other Adverse Effects Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

| Chemical Name | California Hazardous Waste Status |
|-------------------|-----------------------------------|
| Isopropyl alcohol | Toxic |
| 67-63-0 | Ignitable |

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances

DOT

UN/ID No UN1219

Proper Shipping Name Isopropyl alcohol solution

Hazard Class 3
Packing Group II

<u>IATA</u>

UN/ID No UN1219

Proper Shipping Name Isopropyl alcohol solution

Hazard Class 3
Packing Group ||

<u>IMDG</u>

UN/ID No UN1219

Proper Shipping Name Isopropyl alcohol solution

Hazard Class 3
Packing Group II

15. REGULATORY INFORMATION

International Inventories

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

| Chemical Name | CAS No | Weight-% | SARA 313 - Threshold Values % |
|-----------------------------|---------|----------|----------------------------------|
| Isopropyl alcohol - 67-63-0 | 67-63-0 | 99 | 1.0 |

SARA 311/312 Hazard Categories US State Regulations

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|-------------------|------------|---------------|--------------|
| Isopropyl alcohol | X | X | X |
| 67-63-0 | | | |

16. OTHER INFORMATION

U.S. EPA Label Information

| NFPA | Health Hazards | Flammability | Instability | Special Hazards |
|-------------|----------------|----------------|------------------|----------------------------|
| | Not determined | Not determined | Not determined | Not determined |
| <u>HMIS</u> | Health Hazards | Flammability | Physical Hazards | Personal Protection |
| | 1 | 3 | 0 | Not determined |

 Issue Date
 15-Oct-2005

 Revision Date
 28-Feb-2013

Revision Note
New format
Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet
