



PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision date: 06/01/2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Antifreeze & Coolant

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
3100 Sanders Road
Northbrook, IL 60062 - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : 800 424 9300 (United States); 00 1 703 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral), Category 4 H302 Harmful if swallowed.
Specific target organ toxicity — Repeated exposure, Category 2 H373 May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Full text of H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H302 - Harmful if swallowed.
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Precautionary statements (GHS-US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe mist, spray, vapors
P264 - Wash affected areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear personal protective equipment as required.
P301+P310 - If swallowed: Immediately call doctor/physician or poison center
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P405 - Store locked up.
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|---------------------|---------------------|-------------|--|
| ethylene glycol | (CAS-No.) 107-21-1 | 90 - 97 | Acute Tox. 4 (Oral), H302 |
| diethylene glycol | (CAS-No.) 111-46-6 | 0.5 - 5 | Acute Tox. 4 (Oral), H302 STOT RE 2, H373 |
| water | (CAS-No.) 7732-18-5 | 1 - 5 | Not classified |
| denatonium benzoate | (CAS-No.) 3734-33-6 | 30 - 50 ppm | Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Remove contaminated clothing. Wash with plenty of water/... Wash contaminated clothing before reuse. If skin irritation occurs: Rinse immediately with plenty of water (for at least 15 minutes), Get medical advice/attention.
- First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. If eye irritation persists: Get medical advice and attention.
- First-aid measures after ingestion : Obtain emergency medical attention. Rinse mouth. If the person is fully conscious, make him/her drink two glasses of water. Never give an unconscious person anything to drink. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell. If medical advice is delayed, and if the person has swallowed a moderate volume of material (a few ounces), then give three to four ounces of hard liquor, such as whiskey. For children, give proportionally less liquor, according to weight.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Causes damage to organs (kidneys) Oral.
- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after eye contact : Causes serious eye damage.
- Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard. The lethal dose in humans is estimated to be 100 mL (3 oz).

4.3. Indication of any immediate medical attention and special treatment needed

A more effective intravenous antidote for physician uses is 4-methylpyrazole, a potent inhibitor of alcohol dehydrogenases, which effectively blocks the formation of toxic metabolites of ethylene glycol. It has been used to decrease the metabolic consequences of ethylene glycol poisoning before metabolic acidosis coma, seizures, and renal failure have occurred.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water fog. Fine water spray. Foam. Carbon dioxide. Dry chemical powder. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream. May spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Product is not flammable or combustible but may burn under fire conditions.
- Reactivity : No dangerous reactions known under normal conditions of use.

PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Refer to section 8.2.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Store away from other materials.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use. Product may become solid at temperatures below -18 °C (0 °F). Do not store near food, foodstuffs, drugs or potable water supplies. Do not cut, drill, weld, use a blowtorch on, etc. containers even when empty.
- Incompatible products : Keep away from strong acids, strong bases and oxidizing agents.
- Incompatible materials : Sources of ignition.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| ethylene glycol (107-21-1) | | |
|----------------------------|--------------------|---|
| ACGIH | Local name | Ethylene glycol |
| ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ |
| ACGIH | ACGIH TWA (ppm) | 25 ppm (Vapor fraction) |
| ACGIH | ACGIH STEL (mg/m³) | 10 mg/m³ (Inhalable fraction, Aerosol only) |
| ACGIH | ACGIH STEL (ppm) | 50 ppm (Vapor fraction) |
| ACGIH | Remark (ACGIH) | Upper respiratory tract & eye irritant |

diethylene glycol (111-46-6)

Not applicable

PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

denatonium benzoate (3734-33-6)

Not applicable

water (7732-18-5)

Not applicable

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Safety glasses.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Respiratory protection not required in normal conditions. If exposed to levels above exposure limits wear appropriate respiratory protection.



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | : Liquid |
| Color | : Green |
| Odor | : mild |
| Odor threshold | : No data available |
| pH 50% water solution | : 10.5 - 11 |
| Relative evaporation rate (butylacetate=1) | : Nil |
| Freezing point | : -18 °C (0 °F) |
| Boiling point | : 158 °C (317 °F) |
| Flash point | : 116 °C (241 °F) [100% Ethylene Glycol] <i>ASTM D56</i> |
| Auto-ignition temperature | : 400 °C (752 °F) [100% Ethylene Glycol] <i>Literature</i> |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : < 0.1 mm Hg @ 20 °C |
| Relative vapor density at 20 °C | : No data available |
| Specific Gravity | : 1.12 |
| Density | : 1.12 kg/l (9.34 lbs/gal) |
| Solubility | : Water: Complete |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |

PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|----------------------|---------------------|
| Viscosity, dynamic | : No data available |
| Explosive limits | : 3.2 - 15.3 vol % |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Explosive limits | : 3.2 - 15.3 vol % |

9.2. Other information

| | |
|-------------|-------|
| VOC content | : 0 % |
|-------------|-------|

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Extremely high or low temperatures. Keep away from any flames or sparking source.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

10.6. Hazardous decomposition products

alcohols. Carbon dioxide. Carbon monoxide. Fume. alcohols. Aldehydes. Ethers.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|----------------|------------------|
| Acute toxicity | : Not classified |
|----------------|------------------|

| ethylene glycol (107-21-1) | |
|---------------------------------|--|
| LD50 oral rat | 7712 mg/kg bodyweight (according to BASF-internal standards, Rat, Male/female, Experimental value) |
| LC50 inhalation rat (mg/l) | > 2.5 mg/l (6 h, Rat, Male/female, Experimental value) |
| ATE US (oral) | 500 mg/kg bodyweight |
| diethylene glycol (111-46-6) | |
| LD50 oral rat | 19600 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value) |
| LD50 dermal rabbit | 11890 mg/kg (Rabbit) |
| LC50 inhalation rat (mg/l) | > 4.6 mg/l/4h (Other, 4 h, Rat, Weight of evidence) |
| ATE US (oral) | 500 mg/kg bodyweight |
| ATE US (dermal) | 11890 mg/kg bodyweight |
| denatonium benzoate (3734-33-6) | |
| LD50 oral rat | 584 mg/kg (Rat, Literature study) |
| LD50 dermal rabbit | > 2000 mg/kg (Rabbit, Literature study) |
| ATE US (oral) | 584 mg/kg bodyweight |

| | |
|-----------------------------------|------------------|
| Skin corrosion/irritation | : Not classified |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |

| | |
|-----------------------|------------------|
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Not classified |

| | |
|------------------------|---|
| STOT-repeated exposure | : May cause damage to organs (kidneys) through prolonged or repeated exposure (oral). |
|------------------------|---|

PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|--|
| Aspiration hazard | : Not classified |
| Potential adverse human health effects and symptoms | : Based on available data, the classification criteria are not met. |
| Symptoms/effects | : Causes damage to organs (kidneys) Oral. |
| Symptoms/effects after skin contact | : Causes skin irritation. |
| Symptoms/effects after eye contact | : Causes serious eye damage. |
| Symptoms/effects after ingestion | : Swallowing a small quantity of this material will result in serious health hazard. The lethal dose in humans is estimated to be 100 mL (3 oz). |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|--|--|
| ethylene glycol (107-21-1) | |
| LC50 fish 1 | 40,761.00 mg/l (96 h, Salmo gairdneri, Static system) |
| EC50 Daphnia 1 | > 10,000.00 mg/l (24 h, Daphnia magna) |
| diethylene glycol (111-46-6) | |
| LC50 fish 1 | > 5,000.00 ppm (24 h, Carassius auratus) |
| EC50 Daphnia 1 | > 10,000.00 mg/l (24 h, Daphnia magna) |
| LC50 fish 2 | 75,200.00 mg/l (Other, 96 h, Pimephales promelas, Flow-through system, Experimental value) |
| EC50 Daphnia 2 | > 10,000.00 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value) |
| denatonium benzoate (3734-33-6) | |
| LC50 fish 1 | > 1,000.00 mg/l (96 h, Salmo gairdneri, Literature study) |
| EC50 Daphnia 1 | 13.00 mg/l (48 h, Daphnia magna, Literature study) |

12.2. Persistence and degradability

| | |
|--|--|
| ethylene glycol (107-21-1) | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0.47 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.24 g O ₂ /g substance |
| ThOD | 1.29 g O ₂ /g substance |
| BOD (% of ThOD) | 0.36 |
| diethylene glycol (111-46-6) | |
| Persistence and degradability | Biodegradable in the soil. Biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0.02 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.51 g O ₂ /g substance |
| ThOD | 1.51 g O ₂ /g substance |
| BOD (% of ThOD) | 0.02 |
| denatonium benzoate (3734-33-6) | |
| Persistence and degradability | Biodegradability in water: no data available. No (test) data on mobility of the substance available. |

12.3. Bioaccumulative potential

| | |
|-------------------------------------|---|
| ethylene glycol (107-21-1) | |
| BCF fish 1 | 10.00 (72 h, Leuciscus idus) |
| BCF other aquatic organisms 1 | 0.21 - 0.6 (Procambarus sp., Chronic) |
| BCF other aquatic organisms 2 | 190.00 (24 h, Algae) |
| Log Pow | -1.34 (Experimental value) |
| Bioaccumulative potential | Not bioaccumulative. |
| diethylene glycol (111-46-6) | |
| BCF fish 1 | 100.00 (Other, 3 day(s), Leuciscus melanotus, Static system, Fresh water, Experimental value) |

PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| diethylene glycol (111-46-6) | |
|---------------------------------|--|
| Log Pow | -1.98 (Calculated, Other) |
| Bioaccumulative potential | Not bioaccumulative. |
| denatonium benzoate (3734-33-6) | |
| Log Pow | 1.78 (Estimated value) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

12.4. Mobility in soil

| ethylene glycol (107-21-1) | |
|---------------------------------|---|
| Surface tension | 48.00 mN/m (20 °C) |
| Ecology - soil | No (test)data on mobility of the substance available. |
| diethylene glycol (111-46-6) | |
| Surface tension | 0.05 N/m |
| Log Koc | 0.00 (log Koc, SRC PCKOCWIN v1.66, Calculated value) |
| Ecology - soil | Highly mobile in soil. |
| denatonium benzoate (3734-33-6) | |
| Ecology - soil | No (test)data on mobility of the substance available. |

12.5. Other adverse effects

Effect on the ozone layer : No known effect on the ozone layer

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Non Bulk (in quantities under 5,000 lbs in any one inner package):

Not regulated by the US DOT

Bulk (in quantities 5,000 lbs or over in any one inner package):

Transport document description : UN3082 Environmentally hazardous substances, liquid, n.o.s. (Ethylene Glycol), 9, III

UN-No.(DOT) : UN3082

Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s.
Ethylene Glycol

Class (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Packaging Exceptions (49 CFR 173.xxx) : 155

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : No limit

PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : No limit

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Other information : No supplementary information available.

Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

Transport by sea

In accordance with IMDG / IMO

Proper Shipping Name (IMDG) : Not regulated by IMDG (in quantities under 5,000 lbs in any one inner package)

Air transport

In accordance with IATA / ICAO

Proper Shipping Name (IATA) : Not regulated by IATA (in quantities under 5,000 lbs in any one inner package)

SECTION 15: Regulatory information

15.1. US Federal regulations

| PEAK Concentrate Antifreeze and Coolant Conventional Green Formula | |
|--|--|
| EPA TSCA Regulatory Flag | Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed |
| ethylene glycol (107-21-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. |
| CERCLA RQ | 5000 lb(s) |
| SARA Section 311/312 Hazard Classes | Refer to Section 2 for the OSHA hazard classification Ethylene glycol is subject to Tier I and/or Tier II annual inventory reporting. |
| diethylene glycol (111-46-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| denatonium benzoate (3734-33-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| water (7732-18-5) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

15.2. International regulations

CANADA

| PEAK Concentrate Antifreeze and Coolant Conventional Green Formula | |
|--|--|
| WHMIS Classification | This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS. |

EU-Regulations

No additional information available

National regulations

| PEAK Concentrate Antifreeze and Coolant Conventional Green Formula | |
|---|--|
| DSL (Canada): The intentional ingredients of this product are listed ECL (South Korea): The intentional ingredients of this product are listed. EINECS (Europe): The intentional ingredients of this product are listed ENCS (Japan): The intentional ingredients of this product are listed | |

PEAK Concentrate Antifreeze and Coolant Conventional Green Formula

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

⚠ WARNING: This product can expose you to ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| ethylene glycol (107-21-1) | | | | |
|---|---|---|---|----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | Yes | No | No | |

| ethylene glycol (107-21-1) | |
|--|--|
| U.S. - Massachusetts - Right To Know List | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | |
| U.S. - Pennsylvania - RTK (Right to Know) List | |

| diethylene glycol (111-46-6) | |
|---|--|
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List | |

SECTION 16: Other information

Revision date : 06/01/2018


Full text of H-statements:

| | |
|------|--|
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.