Printing date 10/05/2016 Revised On 10/05/2016

## 1 Identification of the substance and manufacturer

Trade name: **OMAHA ORANGE** BD12580000 **Product code:** 

PC9a Paints and coatings. **Product category** Seymour of Sycamore Manufacturer/Supplier: 917 Crosby Avenue Sycamore, IL 60178 phone: 815-895-9101

www.seymourpaint.com

**Emergency telephone number:** CHEMTEL 1-800-255-3924, or 813-248-0585.

# 2 Hazard(s) identification

## Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

**GHS Hazard pictograms** 

**Precautionary statements** 

GHS02 GHS04 GHS07 GHS08

Signal word Danger

**Hazard statements** Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breath

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention. Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

# 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

Chemical Description:		Description:	This product is a mixture of the substances listed below with nonnazardous additions.	
	Dangerous	s components:		
	67-64-1	Acetone		20.9%
	74-98-6	propane		15.71%
		n-butane		9.23%
		barium sulfate, natural		8.81%
		methyl isobutyl ketone		5.66%
		Glycol Ether EP		5.64%
	107-87-9	Methyl Propyl Ketone		2.89%
	108-65-6	PM acetate		2.64%
		xylene (mix)		2.55%
	110-19-0	Isobutyl Acetate		1.51%

# 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a

doctor. Rinse mouth with water. Do not induce vomiting.

Dizziness

After swallowing:

Most important symptoms and

effects:

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

(Contd. of page 1)

Printing date 10/05/2016 Revised On 10/05/2016

Trade name: OMAHA ORANGE

Protective equipment for

firefighters:

A respiratory protective device may be necessary.

## 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

# 7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

#### 8 Exposure controls/personal protection Components with limit values that require monitoring at the workplace: 67-64-1 Acetone Long-term value: 2400 mg/m³, 1000 ppm PEL (United States GHS) REL (United States GHS) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm TLV (United States GHS) 74-98-6 propane PEL (United States GHS) Long-term value: 1800 mg/m3, 1000 ppm REL (United States GHS) Long-term value: 1800 mg/m3, 1000 ppm refer to Appendix F inTLVs&BEIs book; NIC-EX TLV (United States GHS) 106-97-8 n-butane REL (United States GHS) Long-term value: 1900 mg/m3, 800 ppm Short-term value: (2370) mg/m³, (1000) ppm NIC-EX TLV (United States GHS) 7727-43-7 barium sulfate, natural Long-term value: 15\* 5\*\* mg/m³ \*total dust \*\*respirable fraction PEL (United States GHS) REL (United States GHS) Long-term value: 10\* 5\*\* mg/m3 \*total dust \*\*respirable fraction Long-term value: 5\* mg/m<sup>3</sup> TLV (United States GHS) \*inhalable fraction; E 108-10-1 methyl isobutyl ketone PEL (United States GHS) Long-term value: 410 mg/m<sup>3</sup>, 100 ppm Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm REL (United States GHS) Short-term value: 307 mg/m³, 75 ppm TLV (United States GHS) Long-term value: 82 mg/m³, 20 ppm BEI 107-87-9 Methyl Propyl Ketone PEL (United States GHS) Long-term value: 700 mg/m3, 200 ppm Long-term value: 530 mg/m³, 150 ppm REL (United States GHS) TLV (United States GHS) Short-term value: 529 mg/m³, 150 ppm 108-65-6 PM acetate WEEL (United States GHS) Long-term value: 50 ppm 1330-20-7 xylene (mix) PEL (United States GHS) Long-term value: 435 mg/m<sup>3</sup>, 100 ppm Short-term value: 655 mg/m³, 150 ppm REL (United States GHS) Long-term value: 435 mg/m³, 100 ppm Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm TLV (United States GHS) 110-19-0 Isobutyl Acetate PEL (United States GHS) Long-term value: 700 mg/m³, 150 ppm REL (United States GHS) Long-term value: 700 mg/m³, 150 ppm TLV (United States GHS) Short-term value: 172 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm Ingredients with biological limit values:

# 67-64-1 Acetone

BEI (United States GHS) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 10/05/2016 Revised On 10/05/2016

Trade name: OMAHA ORANGE

108-10-1 methyl isobutyl ketone

BEI (United States GHS) 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

1330-20-7 xylene (mix)

**Breathing equipment:** 

BEI (United States GHS)

1.5 g/g creatinine Medium: urine

Time: end of shift

Parameter: Methylhippuric acids Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Nitrile gloves.

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

# 9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined pH-value: Melting point/Melting range Not determined. Undetermined. Boiling point: -44 °C (-47 °F) Flash point: -19 °C (-2 °F) Extremely flammable. Flammability (solid, gas):

**Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % **Upper Explosion Limit:** 10.9 Vol % Not determined. Vapor pressure:

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscositý: Not determined. **VOC** content: 497.0 g/l / 4.15 lb/gl

VOC content (less exempt solvents): 46.8 % MIR Value: 1.12 Solids content: 32.0 %

# 10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

**Chemical stability:** 

Not fully evaluated. Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available.

Hazardous decomposition: No dangerous decomposition products known.

## 11 Toxicological information

LD/LC50 v	LD/LC50 values that are relevant for classification:							
	106-97-8 n-butane							
	Inhalative LC50/4 h 658 mg/l (rat)							
108-10-1 n	108-10-1 methyl isobutyl ketone							
Oral		2100 mg/kg (rat)						
Dermal	LD50	16000 mg/kg (rab)						
Inhalative	Inhalative LC50/4 h 8.3-16.6 mg/l (rat)							
108-65-6 F	108-65-6 PM acetate							
Oral	LD50	8500 mg/kg (rat)						
Inhalative	LC50/4 h	35.7 mg/l (rat)						
1330-20-7	1330-20-7 xylene (mix)							
Oral	LD50	8700 mg/kg (rat)						

(Contd. on page 4)

# Safety Data Sheet

Printing date 10/05/2016 Revised On 10/05/2016

Trade name: OMAHA ORANGE

Dermal LD50 2000 mg/kg (rbt) Inhalative LC50/4 h 6350 mg/l (rat)

(Contd. of page 3)

110-19-0 Isobutyl Acetate

LD50 4763 mg/kg (rbt)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eve effects: Irritating effect.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

108-10-1 methyl isobutyl ketone 2B 1330-20-7 xylene (mix) 3

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

**UN-Number** UN1950 DOT N/A

DOT Consumer Commodity ORM-D

Aerosols, flammable

1950 Aerosols

Transport hazard class(es):

Class Marine pollutant: No

Special precautions for user: Warning: Gases

**EMS Number:** F-D,S-Ŭ

On passenger aircraft/rail: 75 kg **Quantity limitations** On cargo aircraft only: 150 kg

**Excepted quantities (EQ)** 

Not permitted as Excepted Quantity

Limited quantities (LQ) 1L

**Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

Packaging Group: UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information

**ADR** 

**IMDG** 

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate, natural 108-10-1 methyl isobutyl ketone

1330-20-7 xylene (mix)

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. CPSC:

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

100-41-4 ethyl benzene

**CANADIAN ENVIRONMENTAL** 

PROTECTION ACT:

WHMIS Symbols for Canada:

All hazardous ingredients for this product appear on the Canadian Domestice Substance List. A - Compressed gas

Toxic material causing other toxic effects



(Contd. on page 5)

# Safety Data Sheet

Printing date 10/05/2016 Revised On 10/05/2016

Trade name: (	MAHA ORANGE	
Haue Haille. (		

		(Contd. of page 4)		
EPA:	EPA:			
	Acetone	I		
7727-43-7	barium sulfate, natural	D, CBD(inh), NL(oral)		
	methyl isobutyl ketone	I		
	xylene (mix)	I		
110-19-0	Isobutyl Acetate	D		

16	Oth	er in	form	nation
----	-----	-------	------	--------

Contact: Regulatory Affairs Date of preparation / last revision 10/05/2016 / -