

# Safety Data Sheet

# **PERMABOND LH050**

Revision Number: 3

Issue date: 07/27/15

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION** 

Product Name:PERMABOND LH050Product Type:Anaerobic Sealant

Company: PERMABOND LLC 14 Robinson Street Pottstown, PA 19464 USA Telephone: 732-868-1372 or 800-640-7599 Website: www.permabond.com

Emergency Telephone:

Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109 Transport: CHEMTREC 800-424-9300


#### 2. HAZARDS IDENTIFICATION

WARNING:

CAUSES EYE IRRITATION CAUSES SKIN IRRITATION MAY CAUSE AN ALLERGIC SKIN REACTION MAY CASUE RESPIRATORY TRACT IRRITATION

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2B
SKIN IRRITATION	2
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY- SINGLE EXPOSURE- RESPIRATORY SYSTEM	3

PICTOGRAM(S)



Prevention:

**Response:** 

Storage:

Avoid breathing vapors, mist or spray. Wash thoroughly after handling. Use in a well-ventilated area. Wear protective gloves and eye protection. Contaminated clothing should laundered separately.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with plenty of water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF ON SKIN: Rinse with plenty of soap and water.
If feeling unwell call a poison control center or a physician. If eye irritation occurs: Get medical attention.
Store in a well-ventilated cool place.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).



Disposal:	Dispose of according to Federal, State/Provincial and local governmental regulations.
Existing conditions aggravated by exposure:	Skin, eye and respiratory disorders.

### See Section 11 for additional toxicological information.

# **3. COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous components	CAS NUMBER	CONCENTRATION (%)*
Polyglycol dimethacrylate	25852-47-5	60 – 100
Silica, amorphous, fumed crystal free	112945-52-5	1 – 5

\*Exact concentration is a trade secret. Concentration ranges are provided to assist user in determining appropriate protection.

# **4. FIRST AID MEASURES**

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms persist, get medical attention.
Skin contact:	Immediately wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if symptoms occur.
Eye contact:	Immediately flush with large amounts of water for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Keep individual calm and get medical attention. Never give anything by mouth to an unconscious person.
Symptoms:	See section 11

# **5. FIRE-FIGHTING MEASURES**

Extinguishing media:	Foam, water spray or fog, dry chemical or carbon dioxide.
Special fire fighting procedures:	Wear self-contained breathing apparatus and protective clothing. In case of fire keep container cool with water spray.
Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperature resulting in explosions or rupturing containers.
Hazardous combustion products:	Toxic and/or irritating organic vapors may be generated. Oxides of carbon. Oxides of sulfur and oxides of nitrogen.



### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection equipment recommended in section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent product from entering drains or waterways.
Clean-up methods:	Remove all sources of ignition. Evacuate area. Dyke spill to prevent from entering water ways. Ventilate area. Wear protective equipment to clean up. Soak up spill using absorbent material such as sand, silica gel, acid binder, universal binder, or saw dust. Scrape as much material as possible and store in partially filled container until disposal. Refer to section 8 (Exposure Controls/ Personal Protection) before clean up.

### 7. HANDLING AND STORAGE

Handling:Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.<br/>Keep container tightly closed.

Storage: Store in a cool well ventilated area away from heat, sparks, flames, or other sources of ignition. For safe storage store between 0°C (32 °F) and 30°C (86°F)

For shelf life information contact Permabond customer service at (800)714-0170

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employees should complete an assessment of all workplaces to determine the need for and selection of proper exposure controls and protective equipment before each task is started.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Treated fumed silica	10 mg/m3 TWA inhalable dust. 3 mg/m3 TWA	15 mg/m3 TWA Total dust. 5 mg/m3 TWA	None	None
	Respirable fraction.	Respirable fraction		
Engineering controls:	Use local ventilation to maintain	n worker exposure below	established exposure limit	ts.
Respiratory protection:	Use NIOSH approved respirato	or if there is potential to ex	ceed exposure limit(s).	
Skin protection:	Use chemical resistant/ imperm	neable gloves (nitrile) glov	es and protective clothing	to prevent skin contact.
Eye/face protection:	Safety goggles or safety glasses with side shields or face shield if splashing or spraying is expected. Safety showers and eye wash stations should be available.			

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	white
Odor: Odor threshold: pH:	Mild acrylic odor Not Available Not applicable
Vapor pressure:	<5 mm Hg at 24°C (75°F)



Boiling point/range: Melting point/range:	>149ºC (300ºF) Not available
Specific gravity:	1.1 at 23.9°C (75°F)
Vapor density: Flash point: Flammable/Explosive limits – Lower: Flammable/Explosive limits – upper: Autoignition Temperature: Evaporation rate:	Not available >93°C (199.94°F) Not available Not available Not available Not available Not available
Solubility in water:	Slight
Partition coefficient (n-octanol/water): Decomposition temperature: VOC content:	Not available Not available <2 %, 20 grams/liter (Estimated)

# **10. STABILITY AND REACTIVITY**

Stability:	Stable when stored under the recommended storage conditions
Hazardous reactions:	None under normal processing conditions. In the presence incompatible materials or high temperature polymerization may occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Irritating organic vapors.
Incompatible materials:	Strong oxidizing agent, Reducing agents. Acids. Bases. Peroxides. Amines. Free radical polymerizing catalysts. Copper. Iron. Aluminum. Zinc. Rust.
Conditions to avoid:	Contact with incompatible materials which may cause polymerization. Heat, sparks, flames and other sources of ignition.

# **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

## Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapor or mist may cause respiratory tract irritation.
Skin contact:	Causes skin irritation. May cause skin allergic reaction.
Eye contact:	Causes eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.
Existing conditions aggravated by exposure:	Skin, eye and respiratory disorders.

Hazardous components	LD50	LC50	Immediate and delayed Health Effects
Polyglycol dimethacrylate	None	None	Allergen, Irritant
Treated fumed silica	None	None	Irritant

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Polyglycol dimethacrylate	No	No	No
Treated fumed silica	No	No	No



# **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

Not Available

## **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State/Provincial and local governmental regulations. Refer to section 8 (Exposure Controls/Personal Protection) before handling.

# **14. TRANSPORT INFORMATION**

#### U.S. Department of Transportation Ground (49 CFR):

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Exceptions:

Not regulated None None None None

### International Air Transportation (ICAO/IATA):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Exceptions:	None

#### Water Transportation (IMO/IMDG):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
	None

Marine pollutant:

SDS PERMABOND LH050\_Rev3



## **15. REGULATORY INFORMATION**

United States Regulatory Information	
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above the reporting limits.
CERCLA/SARA Section 302 EHS:	None above the reporting limits.
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health, Fire, Reactive
CERCLA/SARA 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right- To-Know Act of 1986 (40 CFR 372).
CERCLA Reportable quantity:	
California Proposition 65:	No chemical listed on the California Proposition 65 are known to be present.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Domestic Substances List.

# **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous one: In section 3

Issue date: 07/27/15

ADDITIONAL INFORMATION: The information given and the recommendations made herein apply to our product(s) alone and are not combined with other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guaranty of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.